



Okoguard®-Okosheath-TS® Medium Voltage Power Cable

5/8kV Shielded Power Cable

One Okopact (Compact Stranded) Copper Conductor/90°C Rating
5kV-133% or 8kV-100% Insulation Level

For Class 1E Nuclear Plant Use



- A Conductor-Stranded Copper
- B Strand Screen-Extruded semi-conducting EPR
- C Insulation-Okoguard
- D Insulation Screen-Extruded semi-conducting EPR
- E Shielding-Coated Copper Tape
- F Cable Tapes
- G Jacket-Okosheath-TS

Insulation

Okoguard is Okonite's registered trade name for its exclusive ethylene-propylene base, thermosetting compound, whose optimum balance of electrical and physical properties is unequalled in other solid dielectrics. The clean red color of Okoguard is the result of an evolutionary development in ethylene-propylene rubber compounding to gain greater dependability of the electrical characteristics.

The triple tandem extrusion of the screens with the insulation provides optimum electrical characteristics.

Jacket

The Okosheath-TS jacket on this cable is a vulcanized chlorinated polyethylene based compound which is mechanically rugged, flame, radiation, and oil resistant.

Applications

Okoguard Shielded-Okosheath-TS power cables are recommended for use as feeder circuits in utility generating plants, in distribution applications and for primary circuits in all industrial and commercial installations.

These cables may be installed in wet or dry locations, indoors or outdoors (exposed to sunlight), in any raceway or underground duct, directly buried, or messenger supported.

Specifications

Conductor: Annealed uncoated compact copper Class B stranded per ASTM B-496.

Strand Screen: Extruded semiconducting EPR strand screen. Meets or exceeds the electrical and physical requirements of ICEA S-97-682, AEIC CS8.

Insulation: Meets or exceeds electrical and physical requirements of ICEA S-97-682, AEIC CS8.

Insulation Screen: Extruded semi-conducting EPR insulation screen applied directly over the insulation. Meets or exceeds electrical and physical requirements of ICEA S-97-682 and CS8.

Shield: Coated 5 mil copper tape helically applied with 25% nominal overlap.

Jacket: Meets or exceeds electrical and physical requirements of ICEA S-93-639 for chlorinated polyethylene jackets.

Product Features

- Qualified as Class 1E cable.
- Okoguard cables meet or exceed all recognized industry standards (AEIC, NEMA/ICEA, IEEE).
- 90°C continuous operating temperature.
- 130°C emergency rating.
- 250°C short circuit rating.
- Cables meet the IEEE 383/IEEE 1202 flame test requirement.
- Quality Assurance traceability
- Excellent corona resistance.
- Radiation resistant.
- Screens are clean stripping.
- Exceptional resistance to "treeing".
- Moisture resistant.
- Resistant to most oils, acids, and alkalies.

Okoguard-Okosheath-TS Medium Voltage Power Cable

Product Data Section 2: Sheet 41

5/8kV Shielded Power Cable

One Okopact (Compact Stranded)
Copper Conductor/ 90°C Rating
5kV-133% or 8kV-100% Insulation Level
For Class 1E Nuclear Plant use

Okoguard Insulation: 115 mils (2.92mm), 5kV—133% or 8kV—100% Insulation Level

Catalog Number	Conductor Size AWG or kcmil		Conductor Size -mm ²		Approx. Dia. over Insulation (In.)		Approx. Dia. over Screen (in.)		Jacket Thickness - mils		Jacket Thickness - mm		Approx. O.D. - Inches		Approx. O.D. - mm		Approx. Net Weight lbs./1000'		Approx. Ship Weight lbs./1000'		Ampacities (1) Conduit in Air		Ampacities (2) Underground Duct		Conduit Size Inches (3)*		
114-23-2627	2/0	67.4	0.65	0.71	80	2.03	0.92	23.4	762	817	210	234	3														
114-23-2629	3/0	85.0	0.70	0.76	80	2.03	1.01	25.7	936	1003	239	266	3														
114-23-2631	4/0	107.0	0.75	0.81	80	2.03	1.06	26.9	1100	1167	272	302	3														
114-23-2633	250	127.0	0.80	0.86	80	2.03	1.12	28.4	1253	1333	300	331	3														
114-23-2637	350	177.0	0.89	0.95	80	2.03	1.21	30.7	1611	1711	362	398	3 1/2														
114-23-2643	500	253.0	1.01	1.07	80	2.03	1.35	34.3	2156	2256	451	479	4														
114-23-2649	750	380.0	1.19	1.26	80	2.03	1.52	38.6	3032	3209	552	580	5														
114-23-2651	1000	507.0	1.34	1.42	80	2.03	1.67	42.4	3880	4057	662	683	5														

Visit Okonite's web site, www.okonite.com for the most up to date dimensions.

Ampacities are from IEEE Std 835-1994 "IEEE Standard Power Cable Ampacities Tables". Values should be determined for the intended installation conditions.

(1) Per table "5 to 15 kV Shielded Single Conductors Extruded Dielectric Power Cable in Conduit in air 90°C conductor 40°C ambient air" No Sun No Wind.

(2) Per table "5 to 15kV Shielded Single Conductor Extruded Dielectric Power Cable in Underground Duct Bank - Triplexed - Single Circuit 25°C Earth Ambient" 90 rho 100% LF.

NOTE: For ampacities for cables installed in tray, see ICEA P-54-440 "Ampacities of Cables Installed in Cable Trays"

(3) Recommended size of rigid or nonmetallic conduit for three conductors based on 40% maximum fill.

*The jam ratio, conduit I.D. to cable O.D. should be checked to avoid possible jamming.