



# Okoguard®-Okoseal® Type MV-105 35kV Shielded Power Cable

One Okopact® (Compact Stranded) Copper Conductor/105°C Rating  
100% and 133% Insulation Level  
For Cable Tray Use-Sunlight Resistant



- A Uncoated, Okopact (Compact Stranded) Copper Conductor
- B Strand Screen-Extruded Semi-conducting EPR
- C Insulation-Okoguard EPR
- D Insulation Screen-Extruded Semi-conducting EPR
- E Shield- Copper Tape
- F Jacket-Okoseal

## Insulation

Okoguard is Okonite's registered trade name for its exclusive ethylene-propylene rubber (EPR) based, thermosetting compound, whose optimum balance of electrical and physical properties is unequaled in other solid dielectrics. Okoguard insulation, with the distinctive red color and a totally integrated EPR system, provides the optimum balance of electrical and physical properties for long, problem free service.

The triple tandem extrusion of the screens with the insulation provides optimum electrical characteristics.

## Jacket

The Okoseal (PVC) jacket supplied with this cable is mechanically rugged and has excellent resistance to flame, oil, acids and most chemicals.

## Applications

Okoguard shielded Okoseal Type MV-105 power cables are recommended for use as feeder circuits, in electric utility generating stations, for distribution circuits, and for feeders or branch circuits in industrial and commercial installations.

Type MV cables may be installed in wet or dry locations, indoors or outdoors (exposed to sunlight), in any raceway or underground duct, directly buried if installed in a system with a grounding conductor in close proximity that conforms with NEC Section 250.4(A)(5) and 311.36, or messenger supported in industrial establishments and electric utilities. Sizes 1/0 AWG and larger may also be installed in cable tray.

## Specifications

**Conductor:** Annealed uncoated copper compact stranded per ASTM B-496.

**Strand Screen:** Extruded EPR semiconducting strand screen. Meets or exceeds electrical and physical requirements of ICEA S-93-639/NEMA WC74 & S-97-682, AEIC CS8, CSA C68.10 and UL 1072.

**Insulation:** Meets or exceeds electrical and physical requirements of ICEA S-93-639/NEMA WC74 & S-97-682, AEIC CS8, CSA C68.10 and UL 1072.

**Insulation Screen:** Extruded EPR semiconducting insulation screen applied directly over the insulation. Meets or exceeds electrical and physical requirements of ICEA S-93-639/NEMA WC74 & S-97-682, AEIC CS8, CSA C68.10 and UL 1072.

**Shield:** 5 mil bare copper tape helically applied with 25% minimum overlap.

**Jacket:** Meets or exceeds electrical and physical requirements of ICEA S-93-639/NEMA WC74 & S-97-682, CSA C68.10 and UL 1072 for polyvinyl chloride jackets.

UL listed as Type MV-105, sunlight resistant, and for use in cable tray in accordance with UL 1072.

CSA C68.10 listed as FT4, SR, LTGG (-40°C), TC (< 500 kcmil) and TC-ER (≥500 kcmil).

## Product Features

- Triple tandem extruded, all EPR system.
- Okoguard cables meet or exceed all recognized industry standards (UL, CSA, AEIC, NEMA/ICEA, IEEE).
- 105°C continuous operating temperature.
- 140°C emergency rating.
- 250°C short circuit rating.
- Passes the Vertical Tray Flame Test requirements of UL 1072 and IEEE 383 and 1202.
- Excellent corona resistance.
- Screens are clean stripping.
- Exceptional resistance to "treeing".
- Exceptional resistance to moisture.
- Resistant to most oils, acids, and alkalis.
- Sunlight resistant.
- For Cable Tray Use.
- Improved Temperature Rating.

# Okoguard -Okoseal Type MV-105

## 35kV Shielded Power Cable

One Okopact (Compact Stranded)

Copper Conductor/105°C Rating

100% and 133% Insulation Level

For Cable Tray Use-Sunlight Resistant



# Product Data

## Section 2: Sheet 57

Catalog Number (1)	Conductor size AWG or kcmil	Conductor Size - mm <sup>2</sup>	Approx. Dia. over Insulation (in.)	Approx. Dia. over Screen (in.)	Jacket Thickness - mils	Jacket Thickness - mm	Approx. O.D. - Inches	Approx. O.D. - mm	Approx. Net Weight lbs./1000'	Approx. Ship Weight lbs./1000'	Ampacities (2) Conduit in Air	Ampacities (3) Underground Duct	Ampacities (4) Cable Tray	Conduit Size Inches (5)
<b>Okoguard Insulation: 345 mils (8.763mm), 100% Insulation Level</b>														
▲ 115-23-3402	1/0	53.5	1.09	1.15	80	2.03	1.34	34.1	1168	1286	215	215	290	4
115-23-3406	2/0	67.4	1.13	1.19	80	2.03	1.38	35.1	1292	1444	255	245	335	4
115-23-3407	3/0	85.0	1.18	1.24	80	2.03	1.43	32.3	1444	1596	290	275	385	4
▲ 115-23-3409	4/0	107.0	1.23	1.29	80	2.03	1.48	37.6	1628	1789	330	315	445	5
115-23-3414	250	127.0	1.28	1.33	80	2.03	1.53	28.8	1789	1973	365	345	495	5
115-23-3416	350	177.0	1.37	1.43	80	2.03	1.62	41.1	2183	2370	440	415	610	5
▲ 115-23-3440	500	253.0	1.48	1.54	80	2.03	1.73	43.9	2732	2960	535	500	765	5
115-23-3441	750	380.0	1.67	1.73	110	2.79	1.98	50.3	3799	4104	655	610	990	6
115-23-3442	1000	507.0	1.87	1.85	110	2.79	2.12	58.8	4708	5833	755	690	1185	6
<b>Okoguard Insulation: 420 mils (10.668mm), 133% Insulation Level</b>														
▲ 115-23-3422	1/0	53.5	1.25	1.31	80	2.03	1.50	38.1	1380	1541	215	215	290	5
▲ 115-23-3426	2/0	67.4	1.29	1.35	80	2.03	1.54	39.1	1509	1693	255	245	335	5
115-23-3427	3/0	85.0	1.34	1.40	80	2.03	1.59	40.4	1667	1851	290	275	385	5
▲ 115-23-3439	4/0	107.0	1.39	1.45	80	2.03	1.64	41.6	1859	2046	330	315	445	5
115-23-3444	250	127.0	1.44	1.50	80	2.03	1.68	42.7	2026	2213	365	345	495	5
▲ 115-23-3446	350	177.0	1.53	1.59	110	2.79	1.84	46.7	2540	2777	440	415	610	5
▲ 115-23-3750	500	253.0	1.63	1.69	110	2.79	1.94	49.3	3100	3405	535	500	765	6
▲ 115-23-3751	750	380.0	1.82	1.90	110	2.79	2.13	54.2	4099	4476	655	610	990	6
115-23-3752	1000	507.0	1.97	2.03	110	2.79	2.28	57.9	5029	5888	755	690	1185	8

Okonite's web site, [www.okonite.com](http://www.okonite.com) contains the most up to date information.

▲ **Authorized stock item.** Available from our Customer Service Centers.

### Aluminum Conductors

(1) Aluminum conductors are available on special order. To order aluminum conductors, change the first three digits of the catalog number from 115 to 135.

### Ampacities

(2) Ampacities are in accordance with Table 311.60(C)(73) of the NEC for three single Type MV-105 conductors, or single conductors twisted together (triplexed) and installed in an isolated conduit in air at an ambient temperature of 40°C and a conductor temperature of 105°C.

(3) Ampacities are in accordance with Table 311.60(C)(77) of the NEC for three single conductors or triplexed cable in one underground raceway, three feet deep with a conductor temperature of 105°C, 100% Load Factor, an ambient earth temperature of 20°C, and thermal resistance (RHO) of 90.

Refer to the NEC, IEEE/CEA S-135 Power Cable Ampacities, or the Okonite Engineering Data Bulletin EHB for installation in duct banks, multiple point ground shields, other ambient temperatures, circuit configurations or installation requirements.

(4) Ampacities for cable in cable tray are in accordance with the NEC, Section 392.80(B)(2)(2), Table 311.60(C)(69) (copper), for single conductor cables installed in a single layer, in uncovered tray, with a maintained spacing of 1 cable OD or more at 105°C conductor temperature and 40°C ambient temperature and multi-point grounding.

(5) Recommended size of rigid or nonmetallic conduit for three conductors based on 40% maximum fill.

\*The jam ratio, conduit I.D. to cable O.D. should be checked to avoid possible jamming.