



X-Olene[®] - FMR Type XHHW-2

600/1000V Power and Control

Copper Conductor/90°C Wet or Dry
Sunlight Resistant



A Bare, Solid or Stranded
Copper Conductor
B X-Olene Insulation

Insulation

X-Olene-FMR is Okonite's trade name for its chemically cross-linked polyethylene insulating compound with outstanding electrical and physical properties. Its excellent chemical physical resistance permits X-Olene's use in areas exposed to alcohol, ketones and dilute acids and bases, without additional coverings.

Applications

X-Olene-FMR Type XHHW-2 600/1000 Volt Cables are recommended for general low voltage power and control applications. Where the National Electrical Code applies, Type XHHW-2 may be used up to 90°C in wet or dry locations. These cables may be installed in wet or dry locations, indoors or outdoors, in raceways, underground ducts, or lashed to a messenger for aerial installation.

Specifications

Conductor: Uncoated soft copper per ASTM B-3. Solid per ASTM B-3. Sizes smaller than #8 are compress stranded per ASTM B-8. Sizes #8 and larger are compact stranded per ASTM B-496..

Insulation: Meets or exceeds all requirements of ICEA S-95-658, NEMA WC-70, and UL Standards.

Listed by Underwriters Laboratories, Inc. as Type XHHW-2.

Product Features

- Small diameter, permits use of smaller conduit or more wires per conduit.
- Excellent heat resistance.
- Rated 90°C in dry or wet locations.
- Mechanically rugged.
- Stable electrical properties.
- Low moisture absorption.
- Highly resistant to weather and most chemicals.
- UL Listed.
- Oil resistant, PR I & PR II.
- Gasoline and oil resistant, GR I & GR II.
- Sunlight resistant.
- VW-1.
- Sizes 1/0 or larger listed for CT-USE.
- -40°C.
- FT4.

X-Olene® - FMR Type XHHW-2

600/1000V Power and Control

Copper Conductor/90°C Wet or Dry
Sunlight Resistant



Product Data

Section 3: Sheet 15

Catalog Number	Conductor size AWG kcmil		Number of Strands	Insulation Thickness - mils	Insulation Thickness - mm		Approx. O.D. - Inches		Approx. O.D. - mm		Approx. Net Weight lbs./1000'	Approx. Ship Weight lbs./1000'	90°C Wet (1)* NEC Ampacity	75°C Wet (1)* NEC Ampacity	ICEA Ampacity (2)
112-36-3251	14	1	30	0.76	0.13	3.30	18	23	15	15	24				
112-36-3261	14	7	30	0.76	0.14	3.56	19	24	15	15	24				
112-36-3271	12	1	30	0.76	0.15	3.81	26	31	20	20	30				
112-36-3281	12	7	30	0.76	0.15	3.81	28	33	20	20	30				
112-36-3291	10	1	30	0.76	0.17	4.32	39	44	30	30	42				
112-36-3301	10	7	30	0.76	0.18	4.57	42	47	30	30	42				
112-36-3221	8	1	45	1.14	0.23	5.84	66	71	55	50	55				
112-36-3331	8	7	45	1.14	0.23	5.84	66	71	55	50	55				
112-36-3351	6	7	45	1.14	0.27	6.89	99	110	75	65	75				
112-36-3371	4	7	45	1.14	0.31	7.87	150	161	95	85	97				
112-36-3391	2	7	45	1.14	0.37	9.40	230	253	130	115	130				
112-36-3401	1	19	55	1.40	0.42	10.7	243	316	150	130	156				
112-36-3411	1/0	19	55	1.40	0.46	11.7	365	404	170	150	179				
112-36-3421	2/0	19	55	1.40	0.50	12.7	451	490	195	175	204				
112-35-3431	3/0	19	55	1.40	0.54	13.7	562	601	225	200	242				
112-36-3441	4/0	19	55	1.40	0.60	15.2	700	739	260	230	278				
112-36-3451	250	37	65	1.65	0.66	16.8	835	868	290	255	317				
112-36-3461	300	37	65	1.65	0.71	18.0	993	1032	320	385	320				
112-36-3471	350	37	65	1.65	0.72	18.3	1150	1209	350	310	384				
112-36-3481	500	37	65	1.65	0.87	22.1	1618	1696	430	380	477				
112-36-3491	750	61	80	2.03	1.07	27.2	2426	2612	535	475	598				
112-36-3501	1000	61	80	2.03	1.22	31.0	3206	3443	615	545	689				

Okonite's web site, www.okonite.com contains the most up to date information.

To order a color other than black, change the last digit of the catalog number as follows:			
White	2	Orange	5
Red	3	Blue	6
Green	4	Yellow	7
Example: To order #14/Sol - Red, the catalog number would be 112-31-3063.			

(1) Ampacities are based on Table 310.16 of the National Electrical Code for these 90°C rated conductors at an ambient temperature of 30°C. The 75°C wet column is provided for additional information.

The ampacities shown apply to open runs of cable, installation in any approved raceway, direct burial in the earth, or as aerial cable on a messenger. Derating for more than three current carrying conductors within a raceway is in accordance with NEC 310.15(C)(1).

(2) Based on three (3) conductors in a single enclosed or exposed conduit. Capacities based on 40°C air ambient using ICEA methods. For 30°C ambient multiply values by 1.10; for 50°C multiply by .90. For other ambients or installation conditions refer to Okonite's Engineering Data Book EHB.

*Current limited to 15, 20 and 30 amps per Section 240.4(D)(3) of the NEC for #14, #12 and #10 AWG, respectively.