



### Okoseal-N Type TC Cable (THHN/THWN-2)

UL Type TC and cUL Type CIC

600V Power and Control Tray Cable



Multiple Copper Conductors With or Without  
grounding Conductor 90°C Dry/90°C Wet

For Cable Tray Use - Sunlight Resistant - For Direct Burial



- A Uncoated Copper Conductors
- B Okoseal Insulation
- C Nylon Conductor Covering
- D Cable Tape
- E Black Okoseal Jacket

#### Insulation

Okoseal® is Okonite's trade name for one of its PVC (polyvinyl chloride) insulating compounds with excellent electrical, mechanical and flame resistant properties.

#### Conductor Jacket

The nylon jacket over the insulation provides excellent mechanical strength and resistance to oil, gasoline and chemicals

#### Cable Jacket

The Okoseal (PVC) jacket is mechanically rugged and has excellent resistance to acids and most chemicals.

#### Applications

Okoseal-N Type TC tray cable is permitted for use on power, lighting, control, and signal circuits; indoors or outdoors; in cable trays, raceways, direct burial in the ground, or where supported in outdoor locations by a messenger wire; for Class 1 circuits as permitted in Article 725 of the NEC; and in cable trays in Class I, Division 2 hazardous locations in industrial establishments where the conditions of maintenance and supervision assure that only qualified persons will service the installation. Not recommended for dc operation in wet locations

#### Specifications

**Conductors:** Uncoated soft copper per ASTM B-3. Sizes smaller than #8 are compress stranded per ASTM B-8. Sizes #8 and larger are compact stranded per ASTM B-496.

**Insulation:** Okoseal insulation with nylon covering per UL 1581.

**Color Coding:** Base colors and tracers as shown on reverse of Data Sheet.

**Assembly:** Conductors cabled in accordance with UL 1277 using fillers, as required, with a cable tape overall.

**Grounding Conductor:** Where indicated, bare stranded copper in accordance with NEC Table 250.122.

**Overall Jacket:** Complies with UL 1277. The Okoseal compound meets or exceeds the requirements of UL 1581.

UL Listed as Type TC cable with a sunlight resistant jacket and for direct burial.

#### Product Features

- For cable tray use.
- For direct burial.
- Sunlight resistant.
- Insulated conductors are UL Listed Type THHN/THWN-2 and rated VW-1.
- UL listed for cable tray use.
- Cable passed the Vertical Tray Flame Test requirements of IEEE 383, UL 1277. Sizes 3/C #8 and larger pass the IEEE 1202 vertical tray flame test requirements.
- 90°C continuous rating in wet or dry locations.
- 130°C emergency overload rating.
- 250°C short circuit rating.
- Okoseal-N Okoseal Type TC cables are quality control inspected to meet or exceed applicable industry standards.
- Resistant to moisture and most chemical atmospheres.
- Thermal stability at elevated temperatures.
- Easy to install and terminate.
- Mechanically rugged.
- High dielectric strength.
- Small diameter, lightweight.
- CSA C22.2 No. 239 Type CIC for sizes 4/0 AWG and smaller
- 1000V CSA Type CIC available for sizes 4/0 AWG and smaller.

# Okoseal-N<sup>®</sup> Type TC Cable (THHN/THWN-2)

UL Type TC and cUL Type CIC

600 Volt Power and Control Tray Cable

Multiple Copper Conductors With or Without

Grounding Conductor 90°C Dry/90°C Wet

For Cable Tray Use - Sunlight Resistant - for Direct Burial



## Product Data Section 4: Sheet 9

Catalog Number	Conductor Size AWG/kcmil	Number of Conductors	Insulation Thickness - mils	Jacket Thickness - mils	Jacket Thickness - mm	Approx. O.D. - Inches	Approx. O.D. - mm	Cross-Sectional Area (sq. in.)†	Approx. Net Weight lbs./1000'	Approx. Ship Weight lbs./1000'	90°C Wet or Dry NEC Ampacity (1)*	75°C Wet NEC Ampacity (1)*		
203-70-3501	14(7X)	Twin	15	45	1.14	0.32	8.2	0.08	65	85	15	15		
203-70-3503		3		45	1.14	0.34	8.6	0.09	80	100	15	15		
203-70-3504		4		45	1.14	0.36	9.3	0.10	100	120	15	15		
203-70-3505		5		45	1.14	0.39	10.0	0.12	120	140	15	15		
203-70-3507		7		45	1.14	0.43	10.8	0.14	155	175	15	14		
203-70-3509		9		45	1.14	0.49	12.4	0.19	200	220	15	14		
203-70-3512		12		60	1.52	0.58	14.7	0.26	275	295	12	10		
203-70-3519		19		60	1.52	0.67	16.9	0.35	405	425	12	10		
203-70-3537		37		80	2.03	0.97	23.2	0.66	775	795	10	8		
203-70-3601		12(7X)		Twin	15	45	1.14	0.36	9.1	0.10	85	105	20	20
203-70-3603				3		45	1.14	0.38	9.6	0.11	110	130	20	20
203-70-3604				4		45	1.14	0.41	10.4	0.13	140	160	20	20
203-70-3605	5		45	1.14		0.44	11.2	0.15	170	190	20	20		
203-70-3607	7		45	1.14		0.48	12.2	0.18	220	240	20	17		
203-70-3609	9		60	1.52		0.59	14.9	0.27	300	320	20	17		
203-70-3612	12		60	1.52		0.65	16.6	0.33	390	410	15	12		
203-70-3619	19		60	1.52		0.76	19.2	0.45	580	600	15	12		
203-70-3637	37		80	2.03		1.09	26.4	0.85	1120	1140	12	10		
203-70-3701	10(7X)		Twin	20		45	1.14	0.43	10.9	0.14	125	145	30	30
203-70-3703			3			45	1.14	0.45	11.5	0.16	165	185	30	30
203-70-3704			4			45	1.14	0.50	12.6	0.19	210	230	30	28
203-70-3705		5	60		1.52	0.57	14.5	0.26	275	295	30	28		
203-70-3707		7	60		1.52	0.62	15.7	0.30	360	380	28	24		
203-70-3709		9	60		1.52	0.72	18.2	0.40	460	480	28	24		
203-70-3712		12	60		1.52	0.80	20.4	0.51	600	620	28	17		

Okonite's web site, [www.okonite.com](http://www.okonite.com) contains the most up to date information.

**Equipment Grounding Conductor:** Any conductor in these cables may be permanently reidentified during installation as the equipment grounding conductor in accordance with Section 250.119(B) of the NEC.

† **Cross-sectional** area for calculation of cable tray fill in accordance with Section 392.22 of the NEC.

### Ampacities (1)

Ampacities are based on Table 310.16 of the National Electrical Code for conductors rated 90°C dry or 75°C wet, in multiple conductor cable at an ambient temperature of 30°C (86°F)

The ampacities shown apply to open runs of cable, installation in any approved raceway, direct burial in the earth, or as aerial cable on a messenger. Derating for more than three current carrying conductors within a the cable is in accordance with NEC 310.15(C)(1).

The ampacities also apply to cables installed in cable tray in accordance with NEC 392.80.

\*Grounds may be split.

\*Current limited to 15, 20 and 30 amps per Section 240.4(D) of the NEC for #14, #12 and #10 AWG, respectively.

# Product Data

## Section 4: Sheet 9

Catalog Number	Conductor Size AWG/kcmil	Number of Conductors	Insulation Thickness - mils	Grounding Thickness - mils	Jacket Conductor AWG*	Jacket Thickness - mils	Jacket Thickness - mm	Approx. O.D. - Inches	Approx. O.D. - mm	Cross-Sectional Area (sq. in.)†	Approx. Net Weight lbs./1000'	Approx. Ship Weight lbs./1000'	90°C Wet or Dry NEC Ampacity (1)	75°C Wet NEC Ampacity (1)
116-70-3103	8(7X)	3	—	60	1.52	0.59	15.0	0.27	253	277	55	50		
116-70-3201		3	10	60	1.52	0.62	15.8	0.30	305	329	55	50		
116-70-3104		4	—	60	1.52	0.65	16.5	0.33	325	364	45	40		
116-70-3205		4	10	60	1.52	0.67	17.0	0.35	375	414	45	40		
116-70-3123	6(7X)	3	—	60	1.52	0.67	17.0	0.35	360	399	75	65		
116-70-3207		3	8	60	1.52	0.70	17.8	0.39	433	472	75	65		
116-70-3124		4	—	60	1.52	0.73	18.5	0.42	465	504	60	52		
116-70-3209		4	8	60	1.52	0.78	19.8	0.48	545	584	60	52		
116-70-3301	4(7X)	3	—	60	1.52	0.81	20.6	0.52	549	588	95	85		
116-70-3303		3	8	60	1.52	0.83	21.1	0.54	630	694	95	85		
116-70-3305		4	—	80	2.03	0.94	23.9	0.69	749	813	76	68		
116-70-3307		4	8	80	2.03	0.97	24.6	0.74	837	901	76	68		
116-70-3311	2(7X)	3	—	80	2.03	0.98	24.9	0.75	842	906	130	115		
116-70-3313		3	6	80	2.03	0.98	24.9	0.75	923	987	130	115		
116-70-3315		4	—	80	2.03	1.07	27.2	0.90	1096	1176	104	92		
116-70-3317		4	6	80	2.03	1.12	28.4	0.99	1232	1312	104	92		

Okonite's web site, [www.okonite.com](http://www.okonite.com) contains the most up to date information.

Okoseal-N Type TC Cable (THHN/THWN-2)  
 UL Type TC and cUL Type CIC  
**600 Volt Power and Control Tray Cable**



**Product Data**  
**Section 4: Sheet 9**

Multiple Copper Conductors, With or Without  
 Grounding Conductor 90°C Dry/90°C Wet  
**For Cable Tray Use - Sunlight Resistant - For Direct Burial**

**Conductor Color Coding Sequence**

Conductor Number	Base Color	Tracer Color
1	Black	
2	Red	
3	Blue	
4	Orange	
5	Yellow	
6	Brown	
7	Red	Black
8	Blue	Black
9	Orange	Black
10	Yellow	Black
11	Brown	Black
12	Black	Red
13	Blue	Red
14	Orange	Red
15	Yellow	Red
16	Brown	Red
17	Black	Blue
18	Red	Blue
19	Orange	Blue
20	Yellow	Blue
21	Brown	Blue
22	Black	Orange
23	Red	Orange
24	Blue	Orange
25	Yellow	Orange
26	Brown	Orange
27	Black	Yellow
28	Red	Yellow
29	Blue	Yellow
30	Orange	Yellow
31	Brown	Yellow
32	Black	Brown
33	Red	Brown
34	Blue	Brown
35	Orange	Brown
36	Yellow	Brown
37	Black	

Color Coding per ICEA  
 Method 1, E-2

**Special Order:** Any or all of the following conductors may be added when specifically requested by the customer to meet their specific application requirements. These conductor codings comply with UL and NEC requirements.

<u>Purpose</u>	<u>Base Color</u>	<u>Tracer Color</u>
Equipment Grounding	Uninsulated Green Green	1 or more continuous yellow stripes
Grounded	White White White White White White	Black continuous stripe Red continuous stripe Blue continuous stripe Orange continuous stripe Brown continuous stripe Numeric Printing