

Loxarmor® Type SP-OS

Type ITC/PLTC Thermocouple Extension Cable

Multiple Pair - Overall Shield — 105°C Rating

For Cable Tray Use



- A** Solid Thermocouple Alloy Conductor
- B** Okoseal Insulation
- C** Tinned Stranded Copper Group Drain Wire
- D** Aluminum/Synthetic Polymer Tape
- E** Twisted Shielded Pairs
- F** Communication Wire
- G** Tinned Stranded Copper Group Drain Wire
- H** Aluminum/Synthetic Polymer Tape
- J** Rip Cord
- K** Inner Okoseal Jacket
- L** Galvanized Steel Interlocking Loarmor
- M** Outer Okoseal Jacket

Specifications

Conductors: Solid alloys per ANSI MC 96.1.

Insulation: Flame-retardant Okoseal® (PVC) per UL 13 and UL 2250, 15 mils nominal thickness, 105°C temperature rating.

Conductor Identification: Pigmented insulation on individual conductors, negative conductor numerically printed for group identification.

Group Shield: Aluminum/synthetic polymer tape overlapped to provide 100% coverage, and a tinned copper drain wire, two sizes smaller than the conductor. All group shields are completely isolated from each other.

Communications Wire: 22 AWG solid 12 mils nominal flame-retardant Okoseal insulation, 105°C temperature rating.

Assembly: Pairs assembled with left-hand lay. Flame-retardant, non-wicking fillers included where required to provide a round cable.

Cable Shield: Aluminum/Polyester tape overlapped to provide 100% coverage, and a 7-strand tinned copper drain wire, same size as the conductor.

Inner Jacket: Color-coded, flame-retardant Okoseal per UL 13 and UL 2250. A rip cord is laid longitudinally under the jacket to facilitate removal.

Loarmor Sheath: An interlocking galvanized steel armor provides mechanical protection against cut-through and crushing. All four sides of the steel tape are galvanized to prevent corrosion.

Outer Jacket: Color-coded, flame-retardant, low temperature Okoseal per UL 13 and UL 2250.

Classification: UL Listed as Type ITC/PLTC - Instrumentation Tray Cable/Power Limited Tray Cable for use in accordance with Article 722 and 335 of the 2023 National Electrical Code.

The cables comply with UL 2250 and UL13 for CL2 and CL3.

Applications

Okonite Loarmor Type SP-OS (Pair - Individual and Overall Shield) thermocouple extension cables are designed for use as instrumentation and process control cables in ITC non-classified or labeled circuits up to 150 volts and 5 amps (750VA) and in Class 2 or 3 Power-Limited circuits where maximum shield-

ing against external interference is required, as well as shielding among groups, particularly where the cable may be subject to abnormally high current or voltage interference; indoors or outdoors; in wet or dry locations with a conductor operating temperatures up to 105°C; in cable trays; in raceways; supported by a messenger wire; under raised floors. Suitable Class I, Division 2, Class II, Division 2, or Class III, Division 1 hazardous locations. Also for use as Power-Limited fire protective signaling cable (FPL) per NEC Article 760. It may be installed in both exposed and concealed work, secured to supports not greater than 6 feet apart.

Product Features

- Passes the UL 1581 & IEEE 383-1974 vertical tray flame tests.
- Passes the IEEE 1202-1991 vertical tray flame test (8 pair and larger).
- Passes the 210,000 BTU/hr vertical tray flame test per ICEA T-29-520 and the 210,000 BTU/hr corner configuration test.
- UL listed as sunlight resistant.
- Complete pre-packaged, factory-tested wiring system-color coded.
- Loarmor cables are quality control inspected to meet or exceed applicable UL Standards.
- Loarmor enclosure permits installation in cable tray containing light and power cables without a barrier separator.
- Individual pairs are numbered and color-coded for simplified hook-up.
- Individual pairs or triads are completely isolated.
- Maximum noise rejection.
- Impervious, continuous sheath excludes moisture, gases and liquids.
- Excellent compression and impact resistance.
- Lower installed system cost than conduit or EMT systems.
- Also available in aluminum.
- Suitable for installation at low temperature to -40°C.

Loxarmor Type SP-OS

Type ITC/PLTC Thermocouple Extension Cable

Multiple Pair - Individual and Overall Shield - 105°C Rating
For Cable Tray Use



Product Data

Section 5: Sheet 27

Conductors: 20 AWG; Okoseal Insulation: 15 mils

	ASA/ISA Type	Catalog Number	Number of Pairs	Inner Jacket Thickness - mils	Inner Jacket Nominal O.D. - In.	Loxarmor O.D. - In. Nominal	Outer Jacket - mils	Nominal Cable O.D. - Inches	Cross-Sectional Area † (sq in)	Approx Net Weight (lbs/1000')	Approx Ship Weight (lbs/1000')
EX	284-10-5504	4	50	.45	.69	50	.80	.50	329	368	
	284-10-5508	8	50	.56	.78	50	.89	.62	431	495	
	284-10-5510	10	60	.64	.86	50	.97	.74	527	591	
	284-10-5512	12	60	.70	.92	50	1.03	.83	566	630	
	284-10-5516	16	60	.77	.98	50	1.09	.93	654	734	
	284-10-5520	20	60	.81	1.03	50	1.14	1.02	745	825	
	284-10-5524	24	70	.97	1.19	50	1.30	1.33	863	969	
	284-10-5536	36	70	1.09	1.32	50	1.43	1.61	1078	1184	
	284-10-5550	50	70	1.19	1.41	50	1.52	1.81	1348	1491	
JX	284-10-5604	4	50	.45	.69	50	.80	.50	329	368	
	284-10-5608	8	50	.56	.78	50	.89	.62	429	493	
	284-10-5610	10	60	.64	.86	50	.97	.74	524	589	
	284-10-5612	12	60	.70	.92	50	1.03	.83	559	623	
	284-10-5616	16	60	.77	.98	50	1.09	.93	651	731	
	284-10-5620	20	60	.81	1.03	50	1.14	1.02	741	821	
	284-10-5624	24	70	.97	1.19	50	1.30	1.33	858	964	
	284-10-5636	36	70	1.09	1.32	50	1.43	1.61	1070	1176	
	284-10-5650	50	70	1.19	1.41	50	1.52	1.81	1338	1481	
KX	284-10-5704	4	50	.43	.69	50	.80	.50	329	368	
	284-10-5708	8	50	.53	.78	50	.89	.62	431	495	
	284-10-5710	10	60	.64	.86	50	.97	.74	527	591	
	284-10-5712	12	60	.67	.92	50	1.03	.83	566	630	
	284-10-5716	16	60	.74	.98	50	1.09	.93	654	734	
	284-10-5720	20	60	.81	1.03	50	1.14	1.02	745	825	
	284-10-5724	24	70	.90	1.19	50	1.30	1.33	863	969	
	284-10-5736	36	70	1.02	1.32	50	1.43	1.61	1078	1184	
	284-10-5750	50	70	1.19	1.41	50	1.52	1.81	1348	1491	
TX	284-10-5804	4	50	.43	.69	50	.80	.50	330	369	
	284-10-5808	8	50	.53	.78	50	.89	.62	433	497	
	284-10-5810	10	60	.64	.86	50	.97	.74	529	593	
	284-10-5812	12	60	.66	.92	50	1.03	.83	564	628	
	284-10-5816	16	60	.73	.98	50	1.09	.93	657	737	
	284-10-5820	20	60	.81	1.03	50	1.14	1.02	749	829	
	284-10-5824	24	70	.90	1.19	50	1.30	1.33	868	974	
	284-10-5836	36	70	1.02	1.32	50	1.43	1.61	1085	1191	
	284-10-5850	50	70	1.19	1.41	50	1.52	1.81	1358	1501	

SX available upon request.

(1) Special grade alloy conductors for JX and TX are available on special order.

† Cross-sectional area for calculation of cable tray fill in accordance with NEC Section 392.22.

Aluminum Loxarmor available on a special order

Length Tolerance: Cut lengths of 1000 feet or longer are subject to a tolerance of ± 10%; less than 1000 feet ± 15%.

ELECTRICAL SPECIFICATIONS	
Per UL Standard 2250	
Insulation Test Voltage (spark test)	5000 Volts ac
Dielectric Test Voltage	1500 Volts ac for 15 sec.
Insulation Resistance Constant @60°F, minimum (natural material typical value).....	2000 Ohms-1000 ft.

ASA/ISA COLOR CODE AND LIMITS OF ERROR										
ASA/ISA Type	Positive Wire		Negative Wire		Outer Jacket Color	Temperature Range °C	Limits of Error		Wire Size (AWG)	Nom. Loop Resistance Per 100' @ 20°C
	Alloy	Color	Alloy	Color			Standard	Special (1)		
EX	Chromel	Purple	Constantan	Red	Purple	0 to 200°C	± 1.7°C	± 1.0°C	20	70.7 ohms
JX	Iron	White	Constantan	Red	Black	0 to 200°C	± 2.2°C	± 1.1°C	20	35.7 ohms
KX	Chromel	Yellow	Alumel	Red	Yellow	0 to 200°C	± 2.2°C	± 1.1°C	20	59.0 ohms
TX	Copper	Blue	Constantan	Red	Blue	-60 to 100°C	± 1.0°C	± 0.5°C	20	29.8 ohms

