



Okonite®-Okoclear-TS® Low Smoke Traction Cable

2000V

Single Copper Conductor/90°C Rating



- A Uncoated, Stranded Copper Conductor
- B Insulation - Okonite
- C Jacket - Okoclear - TS (XLPO)

Insulation

Okonite EPR® insulation is a heat, moisture and chemical resistant, mechanically rugged zero halogenated compound. The insulation thickness is in accordance with ICEA S-95-658, Table 3-4 column A.

Jackets and Finishes

The thermoset jacket supplied with this cable is a cross linked Polyolefin (XLPO) zero halogen - low smoke thermosetting material. It will provide excellent resistance to mechanical abuse, flame, weathering, most oils, acids and alkalis.

Applications

Okonite DC traction cables with low smoke, zero halogen jackets are designed for tunnel and other below grade installations where these features are required. They are also designed for superior aging, and high reliability characteristics.

Specifications

Conductors: Uncoated copper stranded per ASTM B-3. Optional coated copper stranded conductors per ASTM B-33 are also available.

Insulation: Meets or exceeds all requirements of AREMA Signal Manual, Part 10.3.19 and ICEA S-95-658.

Jacket: Cross linked Polyolefin (XLPO) meets the requirements of AREMA Signal Manual Part 10.3.13 and ICEA S-95-658.

Product Features

- Low smoke - zero halogen construction.
- Insulating - non-halogenated Okonite proprietary EPR.
- Extreme heat resistance.
- 90°C Continuous Rating
130°C Emergency Overload Rating
250°C Short Circuit Rating.
- Mechanically Rugged
- Exceptional resistance to deterioration and cut through at high temperatures.
- Meets the flame and smoke release requirements of UL 1685 utilizing the FT4/IEEE 1202 procedure.
- Sunlight Resistant.
- Resistant to oils, weather and most chemical and alkalis.
- Stable electrical properties at high temperatures.
- Voltage rating: 2000 Volts
- 600V, 1000V, 2400V and 5000V cables also available.

Okonite-Okoclear-TS Low Smoke Traction Cable

2000 V

One Copper Conductor/90°C Rating

Product Data Section 7: Sheet 15

Catalog Number	Size kcmil Class C	No. of Strands	Nominal Insulation Thickness (mils)	Jacket Thickness (mils)	Approx. O.D. (In.)	Approx. Net Wt. Lbs./M'	Approx. Ship Wt. Lbs./M'
113-12-2842	500	61	105	65	1.16	1880	1969
113-12-2846	750	91	120	65	1.38	2754	2854
113-12-2850	1000	91	120	95	1.59	3683	3860
113-12-2854	2000	169	140	95	2.09	7122	7681